



UV-B Narrowband TL

TL 20W/01 RS SLV/25

More than 400 independent clinical studies have proven that the UVB Narrowband TL lamps are safer and more effective than any other lamps in their class. That is because these lamps emit only a very narrow waveband from the 'B' bandwidth of the UV spectrum (290 to 315). This narrow waveband is between 305 and 315 nm and peaks at 311 nm: the most efficacious waveband for the treatment of psoriasis. This means that treatment is much more focused and exposure times are much shorter. This in turn leads to a reduction of side effects such as reddening of the skin and itching. All of this makes them ideal for phototherapy treatment of diseases such as psoriasis and vitiligo. What's more, because the overall dosage of this narrowband radiation can be closely controlled, these lamps are suitable for home therapy. N.B.: Our UVB lamps are NOT registered with FDA as medical devices as they are NOT packaged or labeled for commercial distribution for health-related purposes. US customers are referred to the UVB and UVA lamp range brochure US version.

Product data

General Information		Depreciation At 1000 Hours	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Depreciation At 1000 Hours	15 %
Main Application	Phototherapy	Operating and Electrical	
Life To 50% Failures (Nom)	2000 h	Power (Rated) (Nom)	19.3 W
Useful Life (Nom)	2000 h	Lamp Current (Nom)	0.37 A
System Description	Rapid Start	Voltage (Nom)	59 V
Light Technical		UV	
Color Code	01	UV-B Radiation 100 hr (IEC)	2.9 W
Color Designation	Ultra Violet B	UV-B Radiation 5hr (IEC)	3.0 W
Chromaticity Coordinate X (Nom)	208	Product Data	
Chromaticity Coordinate Y (Nom)	192	Full product code	871869666237300
Depreciation At 500 Hours	10 %		

UV-B Narrowband TL

Order product name	TL 20W/01 RS SLV/25
EAN/UPC - Product	8718696662373
Order code	928010000130
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25

Material Nr. (12NC)	928010000130
Net Weight (Piece)	142.800 g

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 20W/01 RS SLV/25	40.5 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

TL 20W/01 RS

Photometric data

Lightcolor /01

Lightcolor /01

UV-B Narrowband TL

